



Stormwater Control Measure (SCM)	
Description: System accepts runoff from a single land use, typically less than 10.0 acres.	
Stormwater Control Measure Type	Description
<p>Biofiltration/ Bioretention (Examples: Basin, Lined rain garden.)</p>	<ul style="list-style-type: none"> • Vegetated feature that filters stormwater through a specialized soil media and includes aggregate surface layer to enhance storage or infiltration. Biofiltration includes an underdrain for discharges where infiltration rates are poor. Allow for inundation of vegetated areas during storm runoff. Indirect infiltration via aggregate subsurface layer and native soil bed. • Vegetation: Yes (50%+) • Location: At-grade, no slope
<p>Vegetated Swale (Examples: Vegetated swale, Grass Swale, Grass Filter Strips, Vegetated Buffer Strips, Bioslopes)</p>	<ul style="list-style-type: none"> • Vegetated feature with up to 4% slope that conveys stormwater and provides water quality filtration by vegetation. Design includes gently sloped flow paths and dense vegetation to promote stormwater surface filtration and velocity reduction by vegetation (settling). Not designed for infiltration. • Vegetation: Yes (50%+) • Location: At-Ground, no slope
<p>Vegetated Buffer Strip (Examples: Vegetated strip)</p>	<ul style="list-style-type: none"> • Gently sloped vegetated feature adjacent to an impervious area that receives stormwater runoff flows as sheet flow. Provides water quality filtration by vegetation. • Vegetation: Yes (70%+) • Location: At-Ground, no slope
<p>Filtration Device (Examples: Catch basin inserts, Drain inserts/inlet filters, FloGard Filter, Stormexx, Ultra-Drain Guard.)</p>	<ul style="list-style-type: none"> • A flow-through structure designed to capture and retain sediment, leaf litter, trash, and coarse particles. Typically accepts runoff from road or a single land use parking lot. • Vegetation: No • Location: Below grade
<p>Infiltration Feature (Examples: Infiltration Trench, Dry Well, Underground Infiltration Chambers)</p>	<ul style="list-style-type: none"> • Structure designed to retain and infiltrate stormwater into unsaturated zones. Existing soil and grades may be modified to sustain maximum infiltration rates. • Vegetation: No • Location: Below Ground

Stormwater Control Measures

Stormwater Control Measure (SCM)	
Description: System accepts runoff from a single land use, typically less than 10.0 acres.	
Stormwater Control Measure Type	Description
<p style="text-align: center;">Pervious Pavement</p> <p>(Examples: Porous Asphalt, Pervious Concrete, Pervious/ Permeable Pavers)</p>	<ul style="list-style-type: none"> • Durable, sustainable materials that create a pervious surface that allows stormwater to infiltrate into the underlying soil. May include an underlying reservoir to increase retention capacity and infiltration rates. Constructed to minimize the volume of stormwater generated. • Vegetation: No • Location: Above Ground
<p style="text-align: center;">Infiltration (Retention) Basin</p> <p>(Examples: Extended Detention, Basin Dry Pond)</p>	<ul style="list-style-type: none"> • A feature designed to store and infiltrate significant volumes of stormwater into unsaturated zone. Infiltration rates may be augmented with a highly permeable substrate. Vegetation distribution is limited to grass or unvegetated. May be below the lowest outlet of a detention basin. • Vegetation: Minimally vegetated or non-vegetated • Location: Above Ground
<p style="text-align: center;">Detention Basin</p> <p>(Examples: Detention Pond)</p>	<ul style="list-style-type: none"> • A flow through basin with discrete inlets and outlets to detain stormwater runoff for some minimum time to reduce peak flows. One or more outlets may exist at different elevations. • Vegetation: Optional • Location: Above Ground
<p style="text-align: center;">Media Filter</p> <p>(Examples: Proprietary Subsurface Filtration Systems: Stormfilter® Perk Filter™ Jellyfish® Tree Box Biofilter (TreePod™), FloGard® Downspout Filter)</p>	<ul style="list-style-type: none"> • A proprietary subsurface flow-through structure that uses a membrane or media to actively filter stormwater pollutants. Pollutant load reductions achieved but no stormwater volume reduction occurs. • Vegetation: No • Location: Primarily Below Ground
<p style="text-align: center;">Treatment Vault</p> <p>(Examples: Hydrodynamic Separator (e.g. Vortechs, CDS®, DVS) Wet Vault Detention)</p>	<ul style="list-style-type: none"> • A subsurface flow-through structure that physically separates sediment, trash, leaf litter, debris or other particulates by separation or settling. Pollutant load reductions achieved but no stormwater volume reduction occurs. • Vegetation: No • Location: Below Ground